www.isis-ex.com









# SPECIALIST HAZARDOUS AREA COMPUTING



TRUSTED, TESTED & RESPECTED

## X CONTROLS

## > ZONE 1 > PC WORKSTATIONS

#### Choose your line, choose your flavor.

Our ATEX-certified Zone 1 series is as versatile as you need it to be.

#### 700, 800 & 900 Ex d for Zones 1 and 2 450 for Zones 1 and 2

- Glove-friendly optional touch screen (800 & 900)
- · Simple to install and will run with most PC operating systems (Window CE on 450)
- Configurable with fiber optic, Cat 5 and/or wireless communications
- High bright (800 and 900) and transflective screen options
- Available with a range of mount and stand configurations
- Ease of field maintenance (with appropriate training)
- Custom solutions available
- Extended temperature options














Zone 1 Accessories



- Intrinsically Safe, Zone 1 and Zone 2
- The keyboard can be directly mounted and hinged on
- Choice of languages







Wireless Access Point

- Lightweight ATEX access point
- Can be used as access point, bridge or repeater
- Quick and easy set-up



www.isis-ex.com

Product Type	PC Workstation	
Model Number	450	
Type of Protection	II 2 G EEx mdeib(ib) IIB+H <sub>2</sub> T4	
Display Size	10.4"	
Display Type	Transreflective TFT LCD	
Display Resolution	640 x 480	
Processor Options	300MHz low power	
HDD/Flash	64Mb System Flash	
RAM	128mb	
Communications Options	WiFi/ethernet/fiber optic	
Keyboard/Mouse/Other	Functional keyboard (F1- F8) 0-9 numeric pad	
Operating Temperature	-40°C to +50°C	
Storage Temperature	-25°C to +55°C	
Ingress Protection	IP66	
Weight	12.5kg / 28lbs	
Dimensions	360 x 260 x 153 mm	

Product Type		PC Workstation
Model Number		700 800 900
Type of Protection		II 2 G Ex d ib [ib] IIB T6 Gb or II 2 G Ex d ib [ib] IIB T4 Gb depending on enclosure front
Display Size	700 800 900	12.1" 15" 19"
Display Type	700 800 900	CCFL backlit LED backlit LED backlit
Display Resolution	700 800 900	XGA 800 x 600 XGA 1024 x 768 SXGA 1280 x 1024
Processor Options	700 800 900	AMD Geode 500MHz 1.8Ghz Pentium M 1.8Ghz Pentium M
HDD/SSD		80Gb/64Gb
RAM	700 800 900	typically 128Mb typically 2Gb typically 2Gb
Communications Options	5	WiFi/ethernet/fiber optic
Keyboard/Mouse/Other		Membrane mouse and k'pad and ext. EEx i interface
Operating Temperature	700 800 900	-20 to +50 -20 to +50 -20 to +50
Storage Temperature		-25°C to +55°C
Ingress Protection		IP66
Weight	700 800 900	23kg/50lbs 33kg/72lbs 40kg/88lbs
Dimensions	700 800 900	369 x 283 x 160 mm 465 x 337 x 160 mm 521 x 390 x 165 mm



## Our Global Sales Network



#### FOR FULL DETAILS OF OUR SUPPORT CENTERS AND THEIR CONTACT DETAILS VISIT OUR WEBSITE www.isis-ex.com/global-sales-partners



AUSTIN > North American Service Center

CALGARY> Sales Partner www.hazlocsolutions.com ABERDEEN> Sales Partner www.wellheads.co.uk

MALTON> Global Headquarters, Service Center & Sales Office www.isis-ex.com

MELBOURNE> Sales Partner www.hazware.com.au

AMSTERDAM > Sales Partner www.dexter.eu

HOUSTON> iSiS-Ex Inc Sales Office www.isis-ex.com



## > WHY iSiS-Ex?

## Because we build better solutions.



We wouldn't say it if we didn't believe it.

More importantly, we wouldn't say it if we couldn't back it up.

We have more than 20 years' experience as oil and gas industry HMI specialists. Our products are field tested and proven to perform in the harshest conditions. We're the brand of choice for market leading oil companies the world over.

Our engineers are constantly innovating. Our Zone 2 HMI is best-in-class, designed and built to give you what you need. As is our feature-rich Wireless Access Point.

Our Zone 1 products have ATEX certification and our Zone 2 products are certified as ATEX, IECEx and CSA Class 1 Zone 2 AEx compliant.

We control quality by managing the entire design and build process – beginning to end. Everything is assembled by us and every product that leaves the building has been subjected to the most rigorous quality assurance process imaginable. We should know – we designed that too.