



# isis-Ex<sup>TM</sup>

SPECIALIST HAZARDOUS  
AREA COMPUTING



TRUSTED, TESTED & RESPECTED

# > WHY iSiS-Ex?

Because we build better solutions.



We wouldn't say it if we didn't believe it.

More importantly, we wouldn't say it if we couldn't back it up.

We have more than 20 years' experience as oil and gas industry HMI specialists. Our products are field tested and proven to perform in the harshest conditions. We're the brand of choice for market leading oil companies the world over.

Our engineers are constantly innovating. Our Zone 2 HMI is best-in-class, designed and built to give you what you need. As is our feature-rich Wireless Access Point.

Our Zone 1 products have ATEX certification and our Zone 2 products are certified as ATEX, IECEx and CSA Class 1 Zone 2 AEx compliant.

We control quality by managing the entire design and build process – beginning to end. Everything is assembled by us and every product that leaves the building has been subjected to the most rigorous quality assurance process imaginable. We should know – we designed that too.


# > ZONE 1 > REMOTE TERMINALS



700, 800 & 900  
Ex d for Zones 1 and 2

- Accepts DVI, VGA, RGB, composite and S-Video input signals
- Optional extended temperature range to -20°C
- Suitable for CCTV applications
- High resolution screen ideal for CCTV
- Available with a range of mounts and stands

Choice of signal input  
Extended temperature  
Ideal for CCTV  
Mounting options



Choice of video inputs  
KVM extender (Cat 5 or fiber)  
Custom solutions available  
Glove-friendly touch screen  
Extended temperature

800 Terminal  
900 Terminal  
800 Monitor  
900 Monitor

●	●	●	●	
●	●	●	●	
●		●		●
●		●		●

Zone 1 Accessories



Keyboard

- Intrinsically Safe, Zone 1 and Zone 2
- Available with touch pad or joystick mouse control
- The keyboard can be directly mounted and hinged on the HMI, or used separately on a desk
- Choice of languages

# > ZONE 1 > MONITORS



- Custom design
- Extended temperature
- Glove-friendly touch screen
- Choice of comms
- Mounting options




Sunshield closed



Hazardous area control of safe area computers  
700, 800 & 900 Ex d for Zones 1 and 2

- Glove-friendly optional touch screen
- Available with fiber optic, Cat 5 and KVM
- Extended fiber range up to 10,000 meters, 300m with Cat 5
- Optional extended temperature range to -20°C
- Available with a range of mounting options
- Wide range of interface and keyboard options available



Wireless Access Point


- Lightweight ATEX access point
- Intrinsically Safe output allows use of any suitably certified antenna in the Zone 1 or Zone 2 hazardous area
- Can be used as access point, bridge or repeater
- Fully configurable to meet statutory WiFi requirements worldwide
- Quick and easy set-up
- Inexpensive way to extend your WiFi network into a hazardous area

Product Type		Remote Terminal	
Model Number		700 800 900	
Type of Protection		II 2 G Ex d ib [ib] IIB T6 Gb or II 2 G Ex d ib [ib] IIB T4 Gb depending on enclosure front	
Display Size	700	12.1"	
	800	15"	
	900	19"	
Display Type		LCD	
Display Resolution	700	XGA 800 x 600	
	800	XGA 1024 x 768	
	900	SXGA 1280 x 1024	
Communications Options		Cat 5/fiber optic	
Video Options		VGA DVI	
Keyboard/Mouse/Other		Membrane mouse and k'pad and ext. Ex i interface	
Operating Temperature		0°C to +45°C	
Storage Temperature		-25°C to +55°C	
Ingress Protection		IP66	
Weight	700	25kg/53lbs	
	800	32kg/68lbs	
	900	44kg/88lbs	
Dimensions	700	369 x 283 x 160 mm	
	800	465 x 337 x 160 mm	
	900	521 x 390 x 165 mm	


Product Type		Monitor	
Model Number		700 800 900	
Type of Protection		II 2 G Ex d ib [ib] IIB T6 Gb or II 2 G Ex d ib [ib] IIB T4 Gb depending on enclosure front	
Display Size	700	12.1"	
	800	15"	
	900	19"	
Display Type		LCD	
Display Resolution	700	XGA 800 x 600	
	800	XGA 1024 x 768	
	900	SXGA 1280 x 1024	
Video Options		DVI, VGA, RBG, composite and S-Video input signals	
Operating Temperature		0°C to +45°C	
Storage Temperature		-25°C to +55°C	
Ingress Protection		IP66	
Weight	700	25kg/53lbs	
	800	32kg/68lbs	
	900	44kg/88lbs	
Dimensions	700	369 x 283 x 160 mm	
	800	465 x 337 x 160 mm	
	900	521 x 390 x 165 mm	



# Our Global Sales Network



FOR FULL DETAILS OF OUR SUPPORT CENTERS AND THEIR CONTACT DETAILS  
VISIT OUR WEBSITE [www.isis-ex.com/global-sales-partners](http://www.isis-ex.com/global-sales-partners)



AUSTIN >  
North American Service Center

ABERDEEN >  
Sales Partner  
[www.wellheads.co.uk](http://www.wellheads.co.uk)

MELBOURNE >  
Sales Partner  
[www.hazware.com.au](http://www.hazware.com.au)

HOUSTON >  
iSiS-Ex Inc Sales Office  
[www.isis-ex.com](http://www.isis-ex.com)

CALGARY >  
Sales Partner  
[www.hazlocsolutions.com](http://www.hazlocsolutions.com)

MALTON >  
Global Headquarters,  
Service Center & Sales Office  
[www.isis-ex.com](http://www.isis-ex.com)

AMSTERDAM >  
Sales Partner  
[www.dexter.eu](http://www.dexter.eu)