

Next generation

REMOTE CONTROL



- **Bright multitouch screen**
- **Easily customizable I/O and software**
- **Integrated camera and sensors**
- **Full day battery life**
- Redundant wireless communication
- Designed for high reliability and safety
- Rugged military-grade design
- Supports industrial communication standards

Vision Remote has a great selection of accessories. Including comfortable harnesses to fit different work tasks, various docking and mounting options and much more.

FEATURES

- Portable
- Wireless
- Easy to use
- Easy to customize
- Bright touchscreen
- High reliability
- Focus on safety



Vision Remote

VM 110

Technical Specifications:

Operating Temperature	-20 - 50 °C
Ingress Protection	IP56
Camera	1280x720 @ 30 Hz
Display	1024x768 Impact Breakage resistant Daylight Viewable PCAP multi-touch. Usable with thin gloves
Operator Feedback	Haptic feedback in each handle. Audio buzzer
Sensors	Accelerometers and gyroscope to detect tilting, free fall and shocks
Operating System	Linux
Software Platform	Create your own apps or use our standard apps. Built with Qt. VisionLink API for secure communication.
Radio	VisionLink - Proprietary redundant radio link consisting of: High Reliability Safety 868 Mhz or 434 Mhz 802.11n WiFi supporting 2.4 Ghz and 5.8 Ghz
Machine Control Interfaces	Profibus DP, ProfiNet, UDP/IP and more
Battery	More than 6 hours. Hot-swappable. Charged in docking station or via cable
Carrying options	Ergonomic Design for carrying by hands. Carrying Harness w/ integrated tilt available.
Dimensions	40,6 x 25,2 x 7,95 cm
Weight	2,6 kg (5.64 lbs)
Stop Function	EN ISO 13849-1 PLd cat.3

